Hisense HVAC



Aeolus Fixed Speed

THE SMARTER WAY TO STAY COOL.



Easy Installation
Designed for quicker and simpler setup.

Horizontal Auto Swing
Balanced Cooling

ON & OFF Function
Set Your Schedule

Easy Maintenance
Designed for quick cleaning and simple upkeep.

Auto Restart
Automatically restarts after power recovery.

Super Mode
Rapid cooling for instant comfort.

Dual Drainage
Flexible drainage options for easy maintenance.

One Button Dehumidification
Humidity Control

Timer 24h
Your comfort, your schedule.



Fixed Speed Type		AS-09HW4SYRCK00 Heat pump	AS-12HW4SVRCK04 Heat pump	AS-18HW4SXSCK01 Heat pump	AS-22HW4SBTCK00 Heat pump
RATINGS					
Cooling Capacity	W	2500	3200	5000	6100
Heating Capacity	W	2600	3300	5200	6250
Power Input-Cooling	W	810	1050	1625	2000
Power Input-Heating	W	695	960	1510	1825
Moisture Removal	L/H.r	-	-	-	-
Air Circulation	CMH Max	600	580	950	1100
EER for Cooling	W/W	3.09	3.05	3.08	3.05
COP for Heating	W/W	3.74	3.44	3.44	3.42
Energy Consumption	kWh / year	405	525	812.5	1000
Energy Class for SA	Cooling	B	B	B	B
Energy Class for SA	Heating	A++	A+	A+	A+
Refrigerant		R410A	R410A	R410A	R410A
Refrigerant Volume	g	620	700	1250	1430
Indoor Unit Noise Level	High (dB (A)) Low (dB (A))	38 -	39 -	43 -	45 -
Outdoor Unit Noise Level	dB (A)	51	53	54	57
POWER SUPPLY					
Voltage, Frequency, Phase		220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V/50Hz
Rated Current	Cooling (A) Heating (A)	3,8 3,3	5,1 4,7	7,3 6,8	8,9 8,2
LRA	A	20	25	41	45
CONNECTING PIPE DIAMETER					
Liquid Pipe	inch	1/4	1/4	1/4	3/8
Gas Pipe	inch	3/8	3/8	1/2	5/8
Maximum Connection Pipe Length	m	15	15	15	15
Maximum Height Difference	m	5	5	5	5
OTHER (VQ PANEL)					
Net Dimensions WxHxD (mm)	Indoor Unit Outdoor Unit	790x197x255 660x482x240	790x197x255 715x482x240	890x220x300 810x585x280	998x225x325 860x650x310
Net Weight (Kg)	Indoor Unit Outdoor Unit	7,5 25	7,5 26	10 41	12,5 42,5
Packing Dimensions WxHxD (mm)	Indoor Unit Outdoor Unit	850x260x320 780x530x345	850x260x320 830x530x345	960x300x365 940x630x385	1060x315x390 995x720x420
Gross Weight (Kg)	Indoor Unit Outdoor Unit	9 27	9 28,5	12 45	15 46,5

Hisense